

## Local Control Station / Visible Break Isolator

Kraus & Naimer has a range of Visible Contact Break Isolators from 63A to 800A, which can be fitted into an IP66, 316 Marine Grade Stainless Steel Enclosure. The Stainless Steel enclosure includes No. 4 finish as standard, an IP66 Safety Laminated Glass viewing window and a sloped roof extending over door design.

## Some other key features include:

- Brand of Isolator Legrand (63A to 800A) or ABB (200A to 800A)
- Polyurethane Pour in Place Gaskets (non-memory)
- Stainless Steel Front or Side Mount Handle
- Stainless Steel Robust Hinges and Locks
- Mild Steel 2mm white base plate
- Panel Construction 1.5mm option 2mm
- LHS Hinged Door

## Options:

- Pushbuttons, terminals, control switches etc.
- Isolator Auxiliary contacts
- Wired to Terminals
- Labelling to Site Standards
- Double Door
- Powder Coat available
- Brass Gland Plates 3 or 6mm or Alloy 4mm.
- Pushbutton activated Internal 24VDC LED's for contact visibility







379 Liverpool Road	14 Brunsdon Street	22 Brookes Street	Unit 9/780-802 South Road
Ashfield, NSW 2131	Bayswater, VIC, 3153	Bowen Hills, QLD 4006	Glandore, SA 5037
Telephone: (02) 9797 7333	Telephone: (03) 9720 9777	Telephone: (07) 3252 8344	Telephone: (08) 8371 1443